




# ALPHA 300

三驱动辊重型辊弯机

*Bending machine with three driving rolls*



**tauring**  
TOP PERFORMING

[www.tauringroup.com](http://www.tauringroup.com)

最大弯曲能力  
Maximum bending capacities

| POSITION | mm                                 | R. mm          | S - O                     |
|----------|------------------------------------|----------------|---------------------------|
| 1a       | 800 x 100                          | 3.000          | ST/SP - SI                |
| 1b       | 300 x 35<br>300 x 60               | 3.200<br>4.800 | ST<br>ST - SI             |
| 2a       | 130<br>175                         | 3.800<br>4.100 | ST<br>ST - SI             |
| 3a       | 200 x 200 x 26<br>250 x 250 x 28   | 2.100<br>4.800 | ST<br>SP - SI             |
| 3b       | 200 x 200 x 26<br>250 x 250 x 28   | 2.100<br>4.800 | ST - AIH<br>SP - AIH      |
| 6a       | UPN 400                            | 4.100          | ST - SI                   |
| 6b       | UPN 400                            | 4.100          | ST - SI                   |
| 6c       | UPN 280<br>UPN 320                 | 6.000<br>8.000 | ST - HEH<br>ST - HEH - SI |
| 7a       | HEA 650                            | 3.000          | ST - SI                   |
| 7a       | HEB 650                            | 3.200          | ST - SI                   |
| 7a       | IPE 600                            | 3.500          | ST - SI                   |
| 7a       | IPN 550                            | 3.000          | ST - SI                   |
| 7h       | HEA 260<br>HEA 340                 | 4.800<br>7.000 | ST - HEH<br>ST - HEH - SI |
| 7h       | HEB 240<br>HEB 300                 | 4.200<br>6.000 | ST - HEH<br>ST - HEH - SI |
| 7h       | IPE 360<br>IPE 450                 | 5.100<br>8.000 | ST - HEH<br>ST - HEH - SI |
| 7h       | IPN 340<br>IPN 400                 | 4.800<br>7.000 | ST - HEH<br>ST - HEH - SI |
| 9b       | 10" gas<br>12" gas                 | 4.000<br>4.600 | RT<br>RT - SI             |
| 9c       | 150<br>200                         | 3.900<br>4.700 | RT<br>RT - SI             |
| 10a      | 260 x 180 x 12<br>400 x 200 x 16   | 3.900<br>4.200 | ST/RQ<br>ST/RQ - SI       |
| 10b      | 250 x 150 x 12<br>300 x 200 x 12,5 | 3.900<br>4.400 | ST/RQ<br>ST/RQ - SI       |
| 11a      | 200 x 200 x 12<br>260 x 260 x 16   | 3.900<br>4.900 | ST/RQ<br>ST/RQ - SI       |

附件工具  
Tools

|  |     |  |        |
|--|-----|--|--------|
|  | S   |  | RO     |
|  | AIC |  | RQ     |
|  | SI  |  | RVT    |
|  | QR  |  | RVQ    |
|  | HEH |  | FT     |
|  | ST  |  | FP     |
|  | SP  |  | WLC    |
|  | RT  |  | ARC 50 |

S: 标配 O: 选配

技术参数  
Technical Data

|  |                                 |
|--|---------------------------------|
|  | mm 1.000                        |
|  | mm 680                          |
|  | min <sup>-1</sup> 1-5           |
|  | kW 52                           |
|  | cm 142*                         |
|  | L x P x H<br>cm 340 x 450 x 370 |
|  | W cm <sup>3</sup> 1680          |
|  | kg 38.000                       |

\* 机器安放需进行地基施工  
Foundation necessary

以上所有参数，可能随厂家的技术研发制造或升级换代需要随时进行修改，恕不另行通知。

Technical data, capacities and specifications are not binding and may be modified without prior notice.



经销商 / Dealer

TAURING S.p.A.  
拓韧中国代表处  
服务热线：400 885 0020  
www.tauringroup.com  
info@tauringroup.com.cn