





注：图片中底座为选配件



BS 40 M

便携式手动辊弯机















Manual bending machine with two driving rolls

















SER
EASY PERFORMING

www.tauringroup.com

最大弯曲能力
Maximum bending capacities

POSITION	mm	R. mm	S - O
 1a	50 x 12	250	ST
 1b	35 x 8	200	ST
 2a	20 x 20	250	ST
 3a	35 x 35 x 4	400	ST
 5a	35 x 35 x 5	200	ST
 4a	30 x 35 x 4	250	ST
 6a	UPN 50	200	ST/SP
 6b	UPN 50	300	ST/SP
 9a	35 x 2	180	RT
 9b	1 gas	400	RT
 9c	22	200	ST/RT
 10a	40 x 20 x 2,5	700	ST/RQ
 10b	30 x 20 x 2,5	600	ST/RQ
 11a	30 x 30 x 2	400	ST/RQ

附件工具
Tools








	ST		RVT
	S		O
	SP		RVQ
	O		O
	RT		BS
	O		ARC 50
	RQ		O

S: 标配 O: 选配

以上所有技术参数，可能随厂家的技术研发制造或升级换代而随时进行修改，恕不另行通知。

Technical data, capacities and specifications are not binding and may be modified without prior notice.

技术参数
Technical Data

	mm 60
	mm 61,8
	mm 86
	mm 108
	cm 40 x 30 x 50
	W cm ³ 1,63 ^{L x P x H}
	kg 54