



图中TOR附件为选配件





DS 60 PLUS

DS 60 PLUS

三驱动辊多功能辊弯机

Bending machine with three driving rolls



SER
EASY PERFORMING

www.tauringroup.com

最大弯曲能力
Maximum bending capacities

POSITION	mm	R. mm	S - O
1a	75 x 30 120 x 30	250 300	ST ST - SI
1b	60 x 20 80 x 15	500 1.000	ST ST - SI
2a	40 50	600 1.000	ST ST - SI
3a	50 x 50 x 8 60 x 60 x 10	500 700	ST ST - SI
3b	50 x 50 x 8 60 x 60 x 10	500 700	ST - AI ST - AI - SI
5a	60 x 60 x 8 80 x 80 x 10	250 400	ST ST - SI
5b	60 x 60 x 8 80 x 80 x 10	250 400	ST ST - SI
6a	UPN 80 UPN 120	500 700	ST SP - SI
6b	UPN 80 UPN 120	500 700	ST SP - SI
9a	70 x 2 80 x 2	900 1.200	RT RT - SI
9b	2" gas 2 1/2" gas	600 1.000	RT RT - SI
9c	50 55	500 900	RT RT - SI
10a	80 x 40 x 3 100 x 40 x 3	500 1.000	ST/RQ ST/RQ - SI - AI
10b	70 x 50 x 3 80 x 40 x 3	600 1.000	ST/RQ ST/RQ - SI
11a	50 x 50 x 4 60 x 60 x 5	900 1.300	ST/RQ ST/RQ - SI
13a	60 x 90 x 50	500	SP - SI



以上所有技术参数，可能随厂家的技术研发制造或升级换代而随时进行修改，恕不另行通知。

Technical data, capacities and specifications are not binding and may be modified without prior notice.

附件工具
Tools

	AI O		RO O
	AIC O		RQ O
	SI O		RVT O
	ROS ROS PLUS O		RVQ O
	AC O		FT O
	AL O		FP O
	TR O		TOR O
	ST S		ATV O
	SP O		ARC 50 O
	RT O		

S: 标配 O: 选配

技术参数
Technical Data

	mm 115
	mm 175
	min ⁻¹ 8-16
	kW 4
	cm 83
	cm 110
	cm $\frac{L \times P \times H}{67 \times 135 \times 149}$
	W cm ³ 21
	kg 490