



图中SI附件为选配件





DS 80 HP



DS 80

三驱动辊多功能辊弯机

Bending machine with three driving rolls



SER
EASY PERFORMING

www.tauringroup.com

最大弯曲能力
Maximum bending capacities

POSITION	mm	R. mm	S - O
1a	140 x 40 150 x 40	300 400	ST ST - SI
1b	100 x 15 100 x 20	600 700	ST ST - SI
2a	50 60	250 400	ST ST - SI
3a	80 x 80 x 8 90 x 90 x 9	300 600	ST/SP SP - SI
3b	80 x 80 x 8 90 x 90 x 9	400 800	ST/SP - AI SP - SI
5a	80 x 80 x 8 90 x 90 x 10	350 400	ST ST - SI
5b	80 x 80 x 8 90 x 90 x 10	350 400	ST ST - SI
6a	UPN 120 UPN 160	300 400	ST/SP SP - SI
6b	UPN 120 UPN 160	300 400	ST/SP SP - SI
6c	UPN 80 UPN 100	600 1.200	ST ST/HE - SI
7a	IPN 100 IPN 140	400 450	ST/SP ST/SP - SI
7b	IPE 80 IPE 100	2.500 4.000	HE - SI HE - SI
9a	80 x 2 90 x 2	1.200 1.500	RT RT - SI
9b	2 1/2" gas 3" gas	550 900	RT RT - SI
9c	60 70	250 400	ST - RT ST/RT - SI
10a	100 x 50 x 4 120 x 60 x 4	800 1.000	ST/RQ ST/RQ - SI
10b	100 x 40 x 3 120 x 60 x 4	800 1.000	ST/RQ RQ - SI
11a	80 x 80 x 3,2 90 x 90 x 4	600 1.000	ST/RQ RQ - SI
13a	70 x 100 x 50	500	SP - SI



附件工具
Tools

	AI		RT
	AIC		RO
	SI		RQ
	ROS		RVT
	HE		RVQ
	AC		FT
	AL		FP
	TR		DRL
	ST		ARC 50
	S		
	SP		

S: 标配 O: 选配

技术参数
Technical Data

	mm 160
	mm 224
	min ⁻¹ 7,7
	kW 5,5
	cm 87
	cm 120
	cm $\frac{L \times P \times H}{105 \times 150 \times 170}$
	W cm ³ 36
	kg 1.020

以上所有技术参数，可能随厂家的技术研发制造或升级换代而随时进行修改，恕不另行通知。

Technical data, capacities and specifications are not binding and may be modified without prior notice.



经销商 / Dealer

TAURING S.p.A.
拓韧中国代表处
服务热线：400 885 0020
www.tauringgroup.com
info@tauringgroup.com.cn